

## IPKAMERE



**HIKVISION**

**HD-TVI Dome kamere za video nadzor**

Naziv artikla	Karakteristike	Cena (gotovinski)	Cena (racun bez PDV)
<b>DS-2CE56C2T-IRM 3,6mm</b>	<p>Antivandal dome kamera            -Čip: Kolor 1/3" CMOS,  <b>1,3 Megapiksela HD 720P</b> (1280x720) rezolucije, 3,6mm optika            -Efektivni pikseli: 1280(H)*720(V)            -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR            -IC osvetljenje: 24 Smart IR dioda dometa do 20 metara, IR cut filter            -Opšte: Napajanje 12V DC, Potrošnja 3,5W            Radna temperatura -40 °C ~+60 °C, IP 66 Dimenzije 89.6 x 59.1 mm,            Težina 400g</p>	<b>39,60</b>	<b>33,00</b>
<b>DS-2CE56D0T-IRM 2,8mm</b>	<p>Antivandal dome kamera            -Čip: Kolor 1/3" CMOS,  <b>2 Megapiksela FULL HD 1080P</b> (1920x1080) rezolucije,2,8mm optika            -Efektivni pikseli: 1920(H)*1080(V)            -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR            -IC osvetljenje: 24 Smart IR dioda dometa do 20 metara, IR cut filter            -Opšte: Napajanje 12V DC, Potrošnja 4W            Radna temperatura -40 °C ~+60 °C, IP 66 Dimenzije 89.6 x 59.1 mm,            Težina 400g</p>	44,40	37,00
<b>DS-2CE56D0T-IRM 3,6mm</b>	<p>Antivandal dome kamera            -Čip: Kolor 1/3" CMOS,  <b>2 Megapiksela FULL HD 1080P</b> (1920x1080) rezolucije,3,6mm optika            -Efektivni pikseli: 1920(H)*1080(V)            -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR            -IC osvetljenje: 24 Smart IR dioda dometa do 20 metara, IR cut filter            -Opšte: Napajanje 12V DC, Potrošnja 3,5W            Radna temperatura -40 °C ~+60 °C, IP 66 Dimenzije 89.6 x 59.1 mm,            Težina 400g</p>	44,40	37,00
<b>DS-2CE56D5T-IRM 2,8mm</b>	<p>Antivandal dome kamera            -Čip: Kolor 1/3" CMOS,  <b>2 Megapiksela FULL HD 1080P</b> (1920x1080) rezolucije,3,6mm optika            -OSD meni: WDR, 3D DNR , DPC , ATW            -Efektivni pikseli: 1930(H)*1088(V)            -Osetljivost: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR            -IC osvetljenje: 24 Smart IR dioda dometa do 20 metara, IR cut filter            -Opšte: Napajanje 12V DC, Potrošnja 3,5W            Radna temperatura -40 °C ~+60 °C, IP 66 Dimenzije 89.6 x 59.1 mm,            mm,            Težina 400g</p>	90,00	75,00

<b>DS-2CE56F7T-ITM 2,8mm</b>	<p>Antivandal dome kamera            -Čip:CMOS  <b>3 Megapiksela (2048x1536) rezolucije</b>,2,8mm optika            -OSD meni:3D DNR , DPC ,ATW, WDR            -Efektivni pikseli: 2052(H)*1536(V)            -Osetljivost: 0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR            -IC osvetljenje: EXIR Smart dioda dometa do 20 metara, IR cut filter            -Opšte: Napajanje 12V DC, Potrošnja 5W            Radna temperatura -30 °C ~+60 °C, IP 66 Dimenzijske 91 x 82.6 x 68,3 mm, Težina 350g</p>	79,20	60,00																												
<b>3 MPIX</b>																															
<b>EXIR</b>	<b>HIKVISION</b>	<b>HD-TVI Bullet kamere za video nadzor</b>																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; padding: 5px;"><b>Naziv artikla</b></th><th style="text-align: left; padding: 5px;"><b>Karakteristike</b></th><th style="text-align: right; padding: 5px;"><b>Cena ( gotovinski )</b></th><th style="text-align: right; padding: 5px;"><b>Cena ( racun bez PDV )</b></th></tr> </thead> <tbody> <tr> <td style="padding: 5px;"><b>DS-2CE16D0T-IR 2,8mm</b></td><td>           Bullet kamera            -Čip:Kolor 1/3" CMOS,  <b>2 Megapiksela FULL HD 1080P (1920x1080) rezolucije</b>,2,8mm optika            -Efektivni pikseli: 1920(H)*1080(V)            -Osetljivost: 0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR            -IC osvetljenje: 24 Smart dioda dometa do 20 metara, IR cut filter            -Opšte: Napajanje 12V DC, Potrošnja 4W            Radna temperatura -30 °C ~+60 °C, IP 66 Dimenzijske 70x149,5 mm,            Težina 360g         </td><td style="text-align: right; padding: 5px;"><b>48,00</b></td><td style="text-align: right; padding: 5px;"><b>40,00</b></td></tr> <tr> <td colspan="2" style="text-align: center; padding: 5px;">  <b>1080P Full HD</b> </td><td></td><td></td></tr> <tr> <td style="padding: 5px;"><b>DS-2CE16D0T-IT3 3,6mm</b></td><td>           Bullet kamera            -Čip:Kolor 1/3" CMOS,  <b>2 Megapiksela FULL HD 1080P (1920x1080) rezolucije</b>,3,6mm optika            -Efektivni pikseli: 1920(H)*1080(V)            -Osetljivost: 0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR            -IC osvetljenje: EXIR Smart dioda dometa do 40 metara, IR cut filter            -Opšte: Napajanje 12V DC, Potrošnja 4W            Radna temperatura -30 °C ~+60 °C, IP 66 Dimenzijske 86x82,8x220mm,            Težina 430g         </td><td style="text-align: right; padding: 5px;">60,00</td><td style="text-align: right; padding: 5px;">50,00</td></tr> <tr> <td colspan="2" style="text-align: center; padding: 5px;"> <b>EXIR</b> <b>1080P Full HD</b> </td><td></td><td></td></tr> <tr> <td style="padding: 5px;"><b>DS-2CE16D1T-AVFIR3</b></td><td>           Bullet kamera            -Čip:Kolor 1/3" CMOS,  <b>2 Megapiksela FULL HD 1080P (1920x1080)</b>            -Optika: varifokal 2,8-12mm            -OSD meni:DNR, AGC, ATW, BLC,            -Efektivni pikseli: 1930(H)*1088(V)            -Osetljivost: 0.01 Lux @ (F1.2,AGC ON),            -IC osvetljenje: 42 Smart dioda dometa do 40 metara,            -Opšte: Napajanje 12V DC, Potrošnja 6W            Radna temperatura -30 °C ~+60 °C, IP66, Dimenzijske            92x84,8x269,6mm,            Težina 1000g         </td><td style="text-align: right; padding: 5px;">92,50</td><td style="text-align: right; padding: 5px;">77,00</td></tr> <tr> <td colspan="2" style="text-align: center; padding: 5px;">  <b>1080P Full HD</b> </td><td></td><td></td></tr> </tbody> </table>				<b>Naziv artikla</b>	<b>Karakteristike</b>	<b>Cena ( gotovinski )</b>	<b>Cena ( racun bez PDV )</b>	<b>DS-2CE16D0T-IR 2,8mm</b>	Bullet kamera -Čip:Kolor 1/3" CMOS, <b>2 Megapiksela FULL HD 1080P (1920x1080) rezolucije</b> ,2,8mm optika -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: 24 Smart dioda dometa do 20 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4W Radna temperatura -30 °C ~+60 °C, IP 66 Dimenzijske 70x149,5 mm, Težina 360g	<b>48,00</b>	<b>40,00</b>	 <b>1080P Full HD</b>				<b>DS-2CE16D0T-IT3 3,6mm</b>	Bullet kamera -Čip:Kolor 1/3" CMOS, <b>2 Megapiksela FULL HD 1080P (1920x1080) rezolucije</b> ,3,6mm optika -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: EXIR Smart dioda dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4W Radna temperatura -30 °C ~+60 °C, IP 66 Dimenzijske 86x82,8x220mm, Težina 430g	60,00	50,00	<b>EXIR</b> <b>1080P Full HD</b>				<b>DS-2CE16D1T-AVFIR3</b>	Bullet kamera -Čip:Kolor 1/3" CMOS, <b>2 Megapiksela FULL HD 1080P (1920x1080)</b> -Optika: varifokal 2,8-12mm -OSD meni:DNR, AGC, ATW, BLC, -Efektivni pikseli: 1930(H)*1088(V) -Osetljivost: 0.01 Lux @ (F1.2,AGC ON), -IC osvetljenje: 42 Smart dioda dometa do 40 metara, -Opšte: Napajanje 12V DC, Potrošnja 6W Radna temperatura -30 °C ~+60 °C, IP66, Dimenzijske 92x84,8x269,6mm, Težina 1000g	92,50	77,00	 <b>1080P Full HD</b>			
<b>Naziv artikla</b>	<b>Karakteristike</b>	<b>Cena ( gotovinski )</b>	<b>Cena ( racun bez PDV )</b>																												
<b>DS-2CE16D0T-IR 2,8mm</b>	Bullet kamera -Čip:Kolor 1/3" CMOS, <b>2 Megapiksela FULL HD 1080P (1920x1080) rezolucije</b> ,2,8mm optika -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: 24 Smart dioda dometa do 20 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4W Radna temperatura -30 °C ~+60 °C, IP 66 Dimenzijske 70x149,5 mm, Težina 360g	<b>48,00</b>	<b>40,00</b>																												
 <b>1080P Full HD</b>																															
<b>DS-2CE16D0T-IT3 3,6mm</b>	Bullet kamera -Čip:Kolor 1/3" CMOS, <b>2 Megapiksela FULL HD 1080P (1920x1080) rezolucije</b> ,3,6mm optika -Efektivni pikseli: 1920(H)*1080(V) -Osetljivost: 0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR -IC osvetljenje: EXIR Smart dioda dometa do 40 metara, IR cut filter -Opšte: Napajanje 12V DC, Potrošnja 4W Radna temperatura -30 °C ~+60 °C, IP 66 Dimenzijske 86x82,8x220mm, Težina 430g	60,00	50,00																												
<b>EXIR</b> <b>1080P Full HD</b>																															
<b>DS-2CE16D1T-AVFIR3</b>	Bullet kamera -Čip:Kolor 1/3" CMOS, <b>2 Megapiksela FULL HD 1080P (1920x1080)</b> -Optika: varifokal 2,8-12mm -OSD meni:DNR, AGC, ATW, BLC, -Efektivni pikseli: 1930(H)*1088(V) -Osetljivost: 0.01 Lux @ (F1.2,AGC ON), -IC osvetljenje: 42 Smart dioda dometa do 40 metara, -Opšte: Napajanje 12V DC, Potrošnja 6W Radna temperatura -30 °C ~+60 °C, IP66, Dimenzijske 92x84,8x269,6mm, Težina 1000g	92,50	77,00																												
 <b>1080P Full HD</b>																															

Naziv artikla	Karakteristike	Cena ( gotovinski )	Cena ( racun bez PDV )
<b>DS-7104HQHI-F1/N</b>	<p>4-KANALNI TURBO HD SNIMAČ (ANALOG + HDTV + AHD)</p> <p>-Rezolucija snimanja: 12fps@1920x1080, 25fps@1280x720; WD1/4CIF</p> <p>-Video/audio ulazi: H.264 video kompresija, 4ch BNC, 1ch audio</p> <p>-Video/audio izlazi: HDMI/VGA (1920X1080/60Hz, 1280x1024/60Hz, 1280x720/60Hz), 1-ch audio, RCA (2.0 Vp-p, 1Ω) (koristi audio ulaz)</p> <p>-Dodatni ulazi: RJ45 mrežni ulaz, 2 USB 2.0 interfejs</p> <p>-Mrežni protokoli: TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS</p> <p>-Hard disk prostor: 1 sata HDD do 4TB kapaciteta</p> <p>-Opšte: Napajanje 12V DC, Potrošnja 15W bez HDD, Radna temperatura -10 °C ~ +55 °C, Dimenzije 200 x 200 x 45mm, Težina 0,8Kg</p> <p>Napomena: Uredaj se može prijaviti na besplatan HIK DDNS</p>	88,80	74,00
<b>DS-7204HQHI-F1/N</b>	<p>4-KANALNI TURBO HD TRIBRID (ANALOG + HDTV + IP + AHD)</p> <p>-Rezolucija snimanja: 12fps@1920x1080, 25fps@1280x720; WD1 /4CIF</p> <p>-Rezolucija snimanja IP kamere: 25fps@1920x1080,</p> <p>-Video/audio ulazi: H.264 video kompresija, 4ch BNC, 1ch audio</p> <p>-Video/audio izlazi: CVBS, HDMI/VGA (1920X1080/60Hz, 1280x1024/60Hz, 1280x720/60Hz), 1-ch audio, RCA (2.0 Vp-p, 1Ω)</p> <p>-Dodatni ulazi: RJ45 mrežni ulaz, RS-485, 2 USB 2.0 interfejs, Mrežni protokoli: TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS</p> <p>-Hard disk prostor: 1 sata HDD do 4TB kapaciteta</p> <p>-Opšte: Napajanje 12V DC, Potrošnja 15W bez HDD, Rad.temp. -10 °C ~+55 °C, Dimenzije 315 x 242 x 45mm, Težina 1,5Kg</p> <p>Napomena: Uredaj se može prijaviti na besplatan HIK DDNS</p>	115,20	96,00
<b>DS-7204HUHI-F1/N</b>	<p>4-KANALNI TURBO HD HIBRID (ANALOG + AHD + HDTV + IP)</p> <p>-Rezolucija snimanja: 15fps@2048x1536, 25fps@1920x1080;720P/WD1/4CIF</p> <p>-Rezolucija snimanja IP kamere:2048x1536,mogućnost dodavanja 2 IP kamere</p> <p>-Video/audio ulazi: H.264 video kompresija, 4ch BNC, 1ch audio</p> <p>-Video/audio izlazi: HDMI/VGA/CVBS (1920X1080/60Hz, 1280x1024/60Hz, 1280x720/60Hz), 1-ch audio</p> <p>-Dodatni ulazi: RJ45 mrežni ulaz, Alarmni ulazi / izlazi 4/1, RS-485, 2xUSB 2.0</p> <p>-Mrežni protokoli: TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS</p> <p>-Hard disk prostor: 1 sata HDD do 4TB kapaciteta</p> <p>-Opšte: Napajanje 12V DC, Potrošnja 15W bez HDD, Radna temperatura -10 °C ~+55 °C, Dimenzije 315x242x45mm, Težina 1,5Kg</p> <p>Napomena: Uredaj se može prijaviti na besplatan HIK DDNS.</p>	151,20	126,00

**DS-7108HQHI-F1/N****TURBO HD 3.0**

## 16-KANALNI TURBO HD (ANALOG + HDTVI + AHD + IP)

-Rezolucija snimanja: 12,5fps@1920x1080, 25fps@1280x720; WD1

/4CIF,

-Video/audio ulazi: H.264 video kompresija, 16ch BNC, 1ch audio

-Video/audio izlazi: HDMI/VGA 4K (3840X2160/30Hz, 2560x1440/60Hz,  
1920x1080/60Hz), 1-ch audio, RCA (2.0 Vp-p, 1Ω)

-Dodatni ulazi: RJ45 mrežni ulaz, RS-485, 2 USB 2.0 interfejs,

-Mrežni protokoli: TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS,

236,40

197,00

NTP, SADP,

SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS

-Hard disk prostor: 1 sata HDD do 4TB kapaciteta

-Opšte: Napajanje 12V DC, Potrošnja 20W bez HDD,

Radna temperatura -10 °C ~+55 °C, Dimenzije 285x210x45mm, Težina

1,2Kg

**DS-7216HQHI-F2/N****TURBO HD 3.0**

## 16-KANALNI TURBO HD TRIBRID (ANALOG + HDTVI + AHD + IP)

-Rezolucija snimanja: 12,5fps@1920x1080, 25fps@1280x720; WD1

/4CIF

-Rezolucija snimanja IP kamere: 25fps@1920x1080,

-Video/audio ulazi: H.264 video kompresija, 16ch BNC, 1ch audio

-Video/audio izlazi: CVBS HDMI/VGA 4K (3840X2160/30Hz,

2560x1440/60Hz), 1-ch audio, RCA (2.0 Vp-p, 1Ω)

-Dodatni ulazi: RJ45 mrežni ulaz, RS-485, 1 USB 2.0 1 USB 3.0 interfejs,

-Mrežni protokoli: TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS,

309,60

258,00

NTP, SADP,

SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS

-Hard disk prostor: 2 sata HDD do 4TB kapaciteta

-Opšte: Napajanje 12V DC, Potrošnja 30W bez HDD,

Radna temperatura -10 °C ~+55 °C, Dimenzije 380x320x48mm, Težina

2Kg

Napomena: Uredaj se može prijaviti na besplatan HIK DDNS

**DS-7216HUHI-F2/N**

-Rezolucija snimanja: 15fps@2048x1536,

25fps@1920x1080;720P/WD1/4CIF

-Rezolucija snimanja IP kamere: 2048x1536, mogućnost dodavanja 2 IP kamere

-Video/audio ulazi: H.264 video kompresija, 16ch BNC, 4ch audio

-Video/audio izlazi: HDMI/VGA/CVBS (4K 3840X2160/30Hz, 2K

2560x1440/60Hz), 1-ch audio

-Dodatni ulazi: RJ45 mrežni ulaz, Alarmni ulazi / izlazi 16/4, RS-485, 1 USB 2.0 interfejs, 1 USB 3.0

488,40

407,00

-Mrežni protokoli: TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS,

NTP, SADP,

SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS

-Hard disk prostor: 2 sata HDD do 4TB kapaciteta

-Opšte: Napajanje 12V DC, Potrošnja 20W bez HDD,

Radna temperatura -10 °C ~+55 °C, Dimenzije 315x242x45mm, Težina

2Kg

Napomena: Uredaj se može prijaviti na besplatan HIK DDNS.

**hikvision****HD-CVI Dome kamere za video nadzor****Naziv artikla****Karakteristike****Cena (gotovinski)****Cena (racun bez PDV)****HAC-HDW1000RP-0280-S3****HD  
720p**

HDCVI kamera, 1 megapiksela, 720P, veoma isplativa, u mini dome kućištu, sa infracvenim diodama 1/4" 1 megapikselski CMOS čip, 25/30fps@720P, veoma brz prenos u realnom vremenu, izbor HD i SD prenosa slike, dan/noć funkcija, ICR filter, AGC, BLC, 2D-DNR,DWDR, objektiv 2.8mm, Smart infracrvene diode maksimalnog dometa do 20m, DC12V

**24,00****19,88****HAC-HDW1100EMP-A-0280-S3****HD  
720p**

HDCVI 720P kamera u vodootpornom dome kućištu, 4 u 1 (HDCV, Analogna, TVI ili AHD), sa smart IC diodama Image Sensor 1/2.9" 1 megapikselski CMOS čip, 25/30fps@720P, ugrađen mikrofon, Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja, dan/noć funkcija, ICR filter, AWB,AGC, BLC, 2DNR, objektiv 3.6mm, Smart IC diode maksimalnog dometa do 50m, DC12V,IP67

**46,50****38,75****HAC-HDW1200RP-0360-S3****1080P  
Full HD**

FULL HD 1080p HDCVI kamera u dome kućištu, 2 megapiksela, 1/2.7" 2Mpx CMOS čip sa progresivnim skeniranjem 1/2.7" 2 megapikselski CMOS čip, 25/30fps@1080P, 25/30/50/60fps@720P veoma brz prenos u realnom vremenu, izbor HD i SD prenosa slike, OSD meni, kontrola putem koaksijalnog kabla, dan/noć funkcija, ICR filter, AWB, AGC, BLC, 3D-DNR, objektiv 3,6mm, Smart infracrvene diode maksimalnog dometa do 20m, DC12V

**39,80****33,13****HAC-HDW1200MP-0360-S3****1080P  
Full HD**

FULL HD 1080p HDCVI kamera u IP67 dome kućištu, 2megapiksela, 1/2.7" 2Mpx CMOS čip sa progresivnim skeniranjem. Maksimalna rezolucija 1920x1080 u 30fps, fiksni megapikselski objektiv 3.6 mm, ICR filter, D-WDR, automatska kontrola bele boje, izbor HD i SD prenosa slike, automatska kontrola pojačanja, 2D redukcija šuma, maksimalni domet IC dioda 30 metara, 12VDC

**47,25****39,38****HAC-HDW1200RP-VF-S3****1080P  
Full HD**

FULL HD 1080p, 2 MP, dome kamera, varifokal, vodootporna, 4 u 1 (HDCV, Analogna, TVI ili AHD) u metalnom IP67 kućištu, sa IC diodama Image Sensor 1/2.7" 2 megapikselski CMOS čip, 25/30fps@1080P, 25/30/50/60fps@720P, veoma brz prenos u realnom vremenu, dan/noć funkcija, ICR filter, AWB, AGC, BLC, 2D redukcija šuma, Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja, varifokalni objektiv 2,7-12mm, Smart infracrvene diode maksimalnog dometa do 30m, IP67, DC12V

**69,70****58,13**

<b>HAC-HDW2221MP-036</b>	  	<b>FULL HD 1080p</b> HDCVI kamera u dome kućištu, 2.1 megapiksela, 1/2.7" 2Mpx CMOS čip sa progresivnim skeniranjem, <b>WDR 120dB</b> 25/30fps@1080P, 25/30/50/60fps@720P, veoma brz prenos u realnom vremenu, izbor HD i SD prenosa slike, OSD meni, kontrola putem koaksijalnog kabla, dan/noć funkcija, ICR filter, AWB, AGC, BLC, 3D-DNR, objektiv 3,6mm, Smart infracrvene diode maksimalnog dometa do 20m, DC12V	63,00	52,50
<b>HAC-HDW2401EMP-0360</b>	 	HDCVI kamera, <b>4.1 megapiksela</b> , Effective Pixels 2688(H)×1520(V), vodootporna, u dome IP67 kućištu, sa smart IC diodama Image Sensor 1/3" CMOS' 4.1 megapikselsni CMOS čip, Max 4MP real-time, 120dB True WDR, 3DNR, HD and SD dual-output, dan/noć funkcija, ICR filter, AWB, AGC, BLC, 2D redukcija šuma, objektiv 3,6mm, Smart infracrvene diode maksimalnog dometa do 50m, IP67, DC12V	109,50	91,25
  <b>HD-CVI Bullet kamere za video nadzor</b>				
<b>Naziv artikla</b>		<b>Karakteristike</b>	<b>Cena ( gotovinski )</b>	<b>Cena (racun bez PDV)</b>
<b>HAC-HFW1000RP-0280-S3</b>	 	HDCVI kamera, <b>1 megapiksel</b> , <b>720P</b> , veoma isplativa, u mini tube kućištu, sa infracrvenim diodama 1/4" 1 megapikselsni CMOS čip, 25/30fps@720P, veoma brz prenos u realnom vremenu, izbor HD i SD prenosa slike, dan/noć funkcija, OSD meni, ICR filter, AGC, BLC, 2D-DNR, DWDR, objektiv 2,8mm, Smart infracrvene diode maksimalnog dometa do 20m, IP67, DC12V	<b>24,00</b>	<b>19,88</b>
<b>HAC-HFW1100DP-0360-S3</b>	 	<b>HD 720p</b> dan/noć HDCVI kamera vodootpornom <b>IP66 bullet</b> kućištu, 1 megapiksel, 4 u 1 (HDCV, Analogna, TVI ili AHD) sa IC diodama Image Sensor 1/2,9" 1 megapiksel CMOS čip, maksimalna rezolucija 1280x720 (720p) u 25fps, veoma brz prenos u realnom vremenu, Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja, ICR filter, automatska kontrola bele boje, automatska kontrola pojačanja, 2D redukcija šuma, ugrađeni megapikselsni fiksni objektiv 3,6mm, minimalno osvetljenje 0 luksa, Smart IC diode, maksimalan domet IC dioda 50 metara, 12VDC	49,50	41,25
<b>HAC-HFW1200SP-0360-S3</b>	 	HDCVI kamera, <b>2 megapiksela</b> , <b>1080P</b> , vodootporna, u IP67 kućištu, sa infracrvenim diodama 1/2,7" 2 megapikselsni CMOS čip, 25/30fps@1080P, veoma brz prenos u realnom vremenu, dan/noć funkcija, ICR filter, AWB, AGC, BLC, 2D redukcija šuma, fiksni megapikselsni objektiv 3,6mm, Smart infracrvene diode maksimalnog dometa do 30m, IP67, DC12V/Max 3.6W	47,20	39,38
<b>HAC-HFW1200DP-0360-S3</b>	 	HDCVI kamera, <b>2 megapiksela</b> , <b>1080P</b> , 4 u 1 (HDCV, Analogna, TVI ili AHD) vodootporna, u IP67 kućištu, sa smart IC diodama Image Sensor 1/2,7" 2 megapikselsni CMOS čip, 25/30fps@1080P, 25/30/50/60fps@720P, veoma brz prenos u realnom vremenu, dan/noć funkcija, Izbor moda rada putem UTC OSD kontrolera ili sa HCVR uređaja, ICR filter, AWB, AGC, BLC, 2D redukcija šuma, fiksni megapikselsni objektiv 3,6mm, <b>Smart infracrvene diode maksimalnog dometa do 80m</b> , IP67, DC12V	64,50	53,75
<b>HAC-HFW2401DP-0360</b>	 	HDCVI kamera, <b>4.1 megapiksela</b> , Effective Pixels 2688(H)×1520(V), vodootporna, u bullet IP67 kućištu, sa smart IC diodama Image Sensor 1/3" CMOS' 4.1 megapikselsni CMOS čip Max 4MP real-time, 120dB True WDR, 3DNR, HD and SD dual-output, veoma brz prenos u realnom vremenu, dan/noć funkcija, ICR filter, AWB, AGC, BLC, 2D redukcija šuma, fiksni megapikselsni objektiv 3,6mm, Smart infracrvene diode maksimalnog dometa do 80m, IP67, DC12V	118,50	98,75

<b>Naziv artikla</b>	<b>Karakteristike</b>	<b>Cena (gotovinski)</b>	<b>Cena (racun bez PDV)</b>
HCVR4104HS-S3	<p>Tribrid digitalni video snimač (podržava analogne, HDCVI i IP kamere), podržava 4 analogne / 1080p HDCVI kamere i jednu dodatnu IP kameru, P2P opcija za lako umrežavanje</p> <p><b>Snimanje analognih i HDCVI kamera u realnom vremenu do rezolucije 1080N (960x1080), mogućnost povezivanja jedne dodatne IP kamere rezolucije 1080p, HDMI/VGA izlaz, izlazna rezolucija do 1920x1080 piksela, 1 audio ulaz, 1 audio izlaz, dvosmerna audio komunikacija, 2 USB porta za bekap i kontrolu mišem, RS485 port za upravljanje PTZ kamerama, mogućnost priključenja jednog SATA hard diska maksimalnog kapaciteta 6TB</b></p>	81,00	67,50
HCVR5104C-S3	<p>Tribrid digitalni video snimač, podržava ukupno 4 analogne ili HDCVI i 2 IP kamere P2P opcija za lako umrežavanje. <b>Real time snimanje u 960H i 720P rezolucijama, snimanje do 15FPS po kameri u 1080P(1920x1080) rezolucija prikaza 1024x768 ili 1920x1080(VGAiHDMI) Realtime prikaz u rezolucijama do 1080P, dual stream, mogućnost snimanja do 2 IP kamere rezolucije 5Mp, maksimalna brzina snimanja ukupno 24 megabita, HDMI/VGA izlaz, izlazna rezolucija do 1920x1080 piksela, 2 USB porta za bekap i kontrolu mišem, RS485 port za kontrolu PTZ kamera, mogućnost priključenja jednog SATA hard diska maksimalnog kapaciteta 6TB</b></p>	103,50	86,25
HCVR4108HS-S3	<p>Tribrid digitalni video snimač (podržava analogne, HDCVI i IP kamere), podržava ukupno 8 kamera bilo kog od navedenih tipova, P2P opcija za lako umrežavanje.</p> <p><b>Real time snimanje u rezolucijama do 960H, snimanje do 12FPS po kameri u 720P (1280x720) + 25FPS zakameru 1 (720p), snimanje analognih kamera u realnom vremenu, mogućnost povezivanja do 2 IP kamere rezolucije 1080p, maksimalna brzina snimanja po kanalu 4 megabita, HDMI/VGA izlaz, izlazna rezolucija do 1920x1080 piksela, 1 audio ulaz, 1 audio izlaz, dvosmerna audio komunikacija, 2 USB porta za bekap i kontrolu mišem, RS485 port za upravljanje PTZ kamerama, mogućnost priključenja jednog SATA hard diska maksimalnog kapaciteta 6TB</b></p>	112,50	93,75
HCVR5108C-S3	<p>Tribrid digitalni video snimač (podržava analogne, HDCVI i IP kamere), podržava ukupno 8 kamera (analogne ili HDCVI) i 4 IP kamere, P2P opcija za lako umrežavanje.</p> <p>Tribrid digitalni video snimač (podržava analogne, HDCVI i IP kamere), podržava ukupno 8 kamera (analogne ili HDCVI) i 4 IP kamere, P2P opcija za lako umrežavanje. <b>Real time snimanje u 960H i 720P rezolucijama, Snimanje do 15FP/S pokameri u 1080P(1920x1080) + 25FP/S za kameru 1, mogućnost snimanja do 4 IP kamere rezolucije do 5 MP, maksimalna brzina snimanja po kanalu 4 megabita, HDMI/VGA izlaz, izlazna rezolucija do 1920x1080 piksela, 1 audio ulaz, 1 audio izlaz, dvosmerna audio komunikacija, 2 USB porta za bekap i kontrolu mišem, RS485 port za kontrolu PTZ kamera, mogućnost priključenja jednog SATA hard diska maksimalnog kapaciteta 6TB</b></p>	148,50	123,75

## **PRATEĆA OPREMA ZA VIDEO NADZOR**

### **Hard diskovi - HDD**

<b>Naziv artikla</b>	<b>Karakteristike</b>	<b>Cena ( gotovinski)</b>	<b>Cena (racun bez PDV)</b>
HARD DISC WD PURPLE 1TB	Western Digital, 1TB Purple, IntelliPower, SATA III, 64MB	78,00	65,00
HARD DISC WD PURPLE 2TB	Western Digital, 2TB Purple, IntelliPower, SATA III, 64MB	114,00	95,00
HARD DISC WD PURPLE4TB	Western Digital, 2TB Purple, IntelliPower, SATA III, 64MB	195,00	162,50

### **Kablovi i konektori**

<b>Naziv artikla</b>	<b>Karakteristike</b>	<b>Cena ( gotovinski)</b>	<b>Cena (racun bez PDV)</b>
RG 59+ 2x0,75	Koaksijalni kabl RG59 sa napojnim kablom 2x0.75	0,49	0,41
RG 59+ 2x0,50	Koaksijalni kabl RG59 sa napojnim kablom 2x0,5	0,38	0,32
	BNC, RG59, krimp, muški	0,43	0,36
	F konektor za RG59 kabl. Pakovanje 100 kom.	0,13	0,11
	BNC konektor muški F ženski. Pakovanje 100 kom.	0,44	0,40

## NAPAJANJA

<i>Naziv artikla</i>	<i>Karakteristike</i>	<i>Cena ( gotovinski )</i>	<i>Cena ( racun bez PDV )</i>
<b>NAPAJANJE XED-1212S</b>			
	12W / 1A / 12V	<b>4,90</b>	<b>4,30</b>
<hr/>			
<b>NAPAJANJE XED-5013S</b>			
	60W / 5A / 12V	11,80	10,50
<hr/>			
<b>9-KANALNO NAPAJANJE</b>			
<b>XED-12012L- 9CH</b>			
	120W / 10A / 12V	50,54	46,25
<hr/>			
<b>16-KANALNO NAPAJANJE</b>			
<b>XED-18012L-16CH</b>			
	180W / 15A / 12V	65,00	56,25
<hr/>			
<b>DC KABL</b>			
	DC utikač	0,44	0,35
<hr/>			
<b><i>RF modulatori</i></b>			
<i>Naziv artikla</i>	<i>Karakteristike</i>	<i>Cena ( gotovinski )</i>	<i>Cena ( racun bez PDV )</i>
<b>MOD-UHF-70</b>			
	A/V modulator CH1 – CH99, PLL, 70dBuV, LED display, napajanje, UF-243	22,35	18,63
<hr/>			
<b>MOD-UHF</b>			
	A/V modulator CH1 – CH99, PLL, 90dBuV, LED display, napajanje, UF-2432	29,85	24,88
<hr/>			
RF modulator + skretnica za veći broj stanova		102,00	85,00
<hr/>			